


TECHNICAL DATASHEET	
Egger Home Laminate Flooring	
8/ 31 Classic	
Coreboard	E1 HCHO HDF swell stopp plus
Profile	UNI fit! Patented The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15 according to Egger Guarantee
Guarantee comercial area	5 according to Egger Guarantee
Antistatic properties according EN1815	yes, < 2 kV
Class of use	31
European Norm EN13329	
Format	CLASSIC
Dimension mm (length x width)	1292 x 192
Complete thickness	8
Thickness of silenzio® special cellulose Bevel	-
Pallet	Packaging Euro
Paket information	
Piece	8
m2	1,98
kg	14,46
Pallet information	
Piece	480
m2	119,07
kg	877,00
Classification and general requirements according EN13329	
Abrasion resistance according EN13329, annex E	AC3 (IP ≥ 2000)
Impact resistance according EN13329, annex H	Big ball: ≥ 500 mm Small ball: ≥ 8 N
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage
Thickness swelling according ISO 24336	≤ 18 %
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1	< 0,05
Surface soundness according EN13329, annex D	≥ 1,0 N/mm2
Thermal resistance according to EN 12667	0,07 m² K/W

